

# EPICa

**EP-2123S/D-S3S3**

**EP-2123S/D-F4S3**

*2U SAS-SAS/FC-SAS Redundant  
RAID Subsystem*



The EP-2123 Series RAID subsystem features 3Gb SAS or 4Gb FC-AL host performance to increase system efficiency and performance. It features high capacity expansion, with 12 hot-swappable SAS/SATA II hard disk drive bays in a 19-inch 2U rackmount unit, scaling to a maximum storage capacity in the terabyte range. The EP-2123D Series also supports dual controllers which provide better fault tolerance and higher reliability of system operation.

## **EXCEPTIONAL MANAGEABILITY**

- The firmware-embedded Web Browser-based RAID manager allows local or remote management and configuration
- The firmware-embedded SMTP manager monitors all system events and user notification automatically
- The firmware-embedded SNMP agent allows remote to monitor events via LAN with no SNMP agent required
- Menu-Driven front panel display
- Innovative Modular architecture

## **FEATURES**

- Supports dual controller for features redundant RAID
- Supports RAID levels 0, 1, 0+1, 3, 5, 6, 30, 50, 60 and JBOD
- Supports online Array roaming
- Online RAID level/stripe size migration
- Online capacity expansion and RAID level migration simultaneously
- Online Volume Set Expansion
- Supports multiple array enclosures per host connection
- Supports greater than 2TB per volume set
- Supports up to 128 LUNs
- Transparent data protection for all popular operating systems
- RAID ADG provides the highest level of data protection
- Instant availability and background initialization
- Supports S.M.A.R.T, NCQ and OOB Staggered Spin-up capable drives
- Local audible event notification alarm.
- Supports password protection
- Serial port interface for remote event notification
- Redundant flash image for high availability
- Support spin down drives when not in use to extend service (MAID)
- Supports Bad Blocks auto remapping and schedule volume check
- Redundant active-active controller functionality ensures zero downtime or data loss
- Fully redundant with hot swappable Controller, disks, cooling fans and power supplies
- Supports hot spare and automatic hot rebuild



# Series Technical Specifications

	<b>EP-2123S/D-S3S3</b>	<b>EP-2123S/D-F4S3</b>
<b>RAID Controller</b>	SAS-SAS	FC-SAS
<b>Controller</b>	Single or Redundant	Single or Redundant
<b>Host Interface</b>	Two 4x mini SAS (3Gb/s)	Two FC-AL (4 Gb/s)
<b>Disk Interface</b>	SAS 3Gb or SATA II	SAS 3Gb or SATA II
<b>SAS expander</b>	4x mini SAS (3Gb/s)	4x mini SAS (3Gb/s)
<b>Capacity</b>		
<b>- Direct Attached</b>	12 Disks	12 Disks
<b>- Expansion</b>	Up to 96 Disks	Up to 96 Disks
<b>Processor Type</b>	Intel IOP341 64-bit	Intel IOP341 64-bit
<b>Cache Memory</b>	512MB~2GB / 1GB~4GB DDR-II ECC SDRAM	
<b>Battery Backup</b>	Optional	Optional
<b>Management Port Support</b>	Yes	Yes
<b>Monitor Port Support</b>	Yes	Yes
<b>RAID Features</b>		
<b>RAID level</b>	0, 1, 0+1, 3, 5, 6, 30, 50, 60 and JBOD	0, 1, 0+1, 3, 5, 6, 30, 50, 60 and JBOD
<b>Array Group</b>	Up to 128	Up to 128
<b>LUNs</b>	Up to 128	Up to 128
<b>Hot Spare</b>	Yes	Yes
<b>Drive Roaming</b>	Yes	Yes
<b>Online Rebuild</b>	Yes	Yes
<b>Variable Stripe Size</b>	Yes	Yes
<b>E-mail Notification</b>	Yes	Yes
<b>Online capacity expansion, RAID level / stripe size migration</b>	Yes	Yes
<b>Online Array roaming</b>	Yes	Yes
<b>Online consistency check</b>	Yes	Yes
<b>SMTP manager and SNMP agent</b>	Yes	Yes
<b>Redundant Flash image</b>	Yes	Yes
<b>Instant availability and background initialization</b>	Yes	Yes
<b>S.M.A.R.T. support</b>	Yes	Yes
<b>MAID</b>	Yes	Yes
<b>Bad block auto-remapping</b>	Yes	Yes
<b>Enclosure</b>		
<b>Platform</b>	Rackmount	Rackmount
<b>Form Factor</b>	2U	2U
<b># of Hot Swap Trays</b>	12	12
<b>Tray Lock</b>	Yes	Yes
<b>Disk Status Indicator</b>	Access / Fail LED	Access / Fail LED
<b>Backplane</b>	SAS / SATA II Single BP	SAS / SATA II Single BP
<b># of PS / Fan Modules</b>	400W x 2 w/PFC	400W x 2 w/PFC
<b># of Fans</b>	2	2
<b>Power Requirements</b>	AC 90V ~ 264V Full Range, 7.5A ~ 4A, 47Hz ~ 63Hz	
<b>Environmental</b>		
<b>Relative Humidity</b>	10% ~ 85% Non-condensing	10% ~ 85% Non-condensing
<b>Operating Temperature</b>	10°C ~ 40°C (50°F ~ 104°F)	10°C ~ 40°C (50°F ~ 104°F)
<b>Physical Dimension</b>	590(L) x 482(W) x 88(H) mm	590(L) x 482(W) x 88(H) mm
<b>Weight (Without Disk)</b>	18.2 / 19.7Kg	18.2 / 19.7Kg

Specification is subject to change without notice.  
All company and product names are trademarks of their respective owners.



**PROWARE TECHNOLOGY CORP.**  
Tel:886-2-2914-8001(Rep.) Fax:886-2-2914-7975  
<http://www.proware.com.tw> E-mail:info@proware.com.tw

**Your Storage Solutions Partner**